

Brench type spirit level
Item No. 4460/080 – 4462/150

Manufacturer:
Roeckle Neigungsmesstechnik e.K.
Lichtäckerstr. 11
D-73770 Denkendorf
Tel. +49 (0)711 311332
Fax +49 (0)711 3161727
E-Mail info@roeckle.com
web www.roeckle.com



Product:
Brench type spirit level. Stable version made of high-quality special casting, structurally lacquered. With flat sole, for easy adjustment of horizontal surfaces. The measuring surface is finely ground. The device is equipped with ground longitudinal vial. This spirit level is equipped with two holes for screwing on M5 screws. The sensitivity of the longitudinal vial is indicated on the type label.

Length	Distance of the holes	Bore hole
80 mm	60 mm	5,3 mm
100 mm	80 mm	5,3 mm
150 mm	125 mm	5,3 mm

Technical information:

Length	mm	80	100	150	
Width / Height	mm	24 / 24	24 / 24	24 / 24	
Weight of the spirit level	kg	0.20	0.26	0.40	
ItemNo. 4460	mountable	0.30 mm/m	X	X	X
ItemNo. 4461	mountable	0.10 mm/m	X	X	X
ItemNo. 4462	mountable	0.04 mm/m	-	-	X

(X = available)

Special designs optional:
With magnets

Accessories:
Custom, robust plastic case for storage (446x/xxx/KK)

Additional service optional:
Measuring protocol

Working/storage temperature:

For precision mechanical spirit levels, the working temperature is 20°C (+/-5 K) and the storage temperature is -40°C to +70°C.

Tolerances according to factory standard (not DIN 877):

0.04 mm/m: $T_{tol} = 20$ microns/m, DoE = 1 Scd
0.1 mm/m: $T_{tol} = 40$ microns/m, DoE = 0.8 Scd
0.3 mm/m: $T_{tol} = 120$ microns/m, DoE = 0.8 Scd

T_{tol} = permissible tolerance, DoE = difference value on envelope, Scd = scale divisions