

Horizontal Precision spirit level adjustable
Item No. 6080/160 – 6084/500

Manufacturer:
Roeckle Neigungsmesstechnik e.K.
Lichtäckerstr. 11
D-73770 Denkendorf
Tel. +49 (0)711 311332
Fax +49 (0)711 3161727
E-Mail info@roeckle.com
web www.roeckle.com



Product:

Adjustable precision spirit level according to DIN 877, adjustment range +/- 5 turns (+/- 4 mm/m). Stable version made of high-quality special casting, structurally lacquered. Measuring surfaces flat and prismatic (150°) finely ground, with ground and divided longitudinal vial with lateral insight. The device is equipped with cross-vial and full heat protection. Suitable for aligning horizontal surfaces and shafts. The sensitivity of the longitudinal vial is indicated on the type label.

Technical information:

Length	mm	160	200	250	300	500
Width / Height	mm	42 / 44	42 / 45	42 / 46	42 / 47	44 / 48
Weight of the water scale	kg	1.03	1.31	1.75	2.17	3.97
Item No. 6080	0.30 mm/m	X	X	X	X	X
Item No. 6081	0.10 mm/m	X	X	X	X	X
Item No. 6082	0.04 mm/m	X	X	X	X	X
Item No. 6083	0.02 mm/m	X	X	X	X	X
Item No. 6084	0.01 mm/m	-	X	X	X	X

(X = available)

Possible shaft diameter: 115.9 mm (max), 19.3 mm (min)

Special designs optional:

- with flat sole
- with magnets
- with holes for screwing on

Accessories:

Custom, robust plastic case for storage (608xxx/KK)

Additional service optional:

Measuring protocol

Working/storage temperature:

For precision mechanical spirit levels, the working temperature is 20°C (+/-5 K) and the storage temperature is -40°C to +70°C.

Tolerances according to DIN 877 depending on the sensitivity at L > 100 mm (L ≤ 100 mm):

0.3 mm/m:	T _{zul} =	60(120) microns/m,	DoE = 0.4 (0.8) Scd
0.1 mm/m:	T _{zul} =	20(40) microns/m,	DoE = 0.4 (0.8) Scd
0.04 mm/m:	T _{zul} =	10(10) microns/m,	DoE = 0.5 (0.5) Scd
0.02 mm/m:	T _{zul} =	10(10) microns/m,	DoE = 1.0 (1.0) Scd
0.01 mm/m:	T _{zul} =	10(10) microns/m,	DoE = 2.0 (2.0) Scd

T_{zul} = permissible tolerance, DoE = difference value on envelope, Scd = scale divisions