

Aluminium spirit level mountable
Item No. 4640/080 – 4641/080

Manufacturer:
Roeckle Neigungsmesstechnik e.K.
Lichtäckerstr. 11
D-73770 Denkendorf
Tel. +49 (0)711 311332
Fax +49 (0)711 3161727
E-Mail info@roeckle.com
web www.roeckle.com



Product:

Mountable spirit level made of aluminium, with flat sole, for easy adjustment of horizontal surfaces. The surface is black anodized. The device is equipped with ground and split longitudinal vial. The sensitivity of the longitudinal vial is indicated on the type label.

Technical information:

Length	mm	80
Width / Height	mm	16 / 16
Weight of the spirit level	kg	0.04
Item No. 4640	0.40 mm/m	X
Item No. 4641	0.10 mm/m	X

(X = available)

Bore distance 70 mm for M3 countersunk head screws, bore diameter 3.4 mm

Accessories:

Case for storage included in delivery

Additional power optional:

Measuring protocol

Working/storage temperature:

For precision mechanical spirit levels, the working temperature is 20°C (+/-5 K) and the storage temperature is -40°C to +70°C.

Tolerances according to factory standard (not DIN 877):

0.4 mm/m: $T_{tol} = 160$ microns/m, DoE = 0.8 Scd

0.1 mm/m: $T_{tol} = 40$ microns/m, DoE = 0.8 Scd

T_{tol} = permissible tolerance, DoE = difference value on envelope, Scd = scale divisions