

MICROLEVEL electronic precision spirit level with remote functions Item No. 5523/200/KK - 5525/200/KK

Manufacturer: Roeckle Neigungsmesstechnik e.K. Lichtäckerstr. 11 D-73770 Denkendorf Tel. +49 (0)711 311332 Fax +49 (0)711 3161727 E-Mail info@roeckle.com web www.roeckle.com



Product:

Stable version made of high-quality special casting, structurally

lacquered. With prismatic (154°) base, for aligning horizontal shafts with large diameter. The measuring surfaces are finely ground. The battery-powered device is equipped with an inclination sensor and an electronic with large, easy-to-read color display for longitudinal and transverse inclination and full heat protection. It has interfaces for communication with external display devices or PC via USB and Bluetooth for remote display, measurement protocol, data export MS-Excel.

Technical information:

mm	200
mm	160/83
kg	4.10
kg	4.90
·	
0.02 mm/m	
0.01 mm/m	
0.005 mm/m	
54 mm / 690 mm	
20/10/5 microns for unit mm/m depending on the model, 1	micron at the
unit mm/200 mm	
Color, Diagonal 46 mm / 1.8"	
fmax = 0.04% of MW, min. 0.01% of ME / 0.05%/h of ME	
+/- 15 degrees (approx. +/- 261 mm/m)	
< 3 seconds	
0.1% of ME per °C	
20°C +/- 10K	
from -30°C to +70°C	
Bluetooth and USB 2.0 Micro A	
Li-ion battery approx.10h uptime	
According to DIN 877 and DIN 2276-2, CE compliant and I	EMC-tested
MW = measured value, ME = measuring range end value	
	mm kg kg 0.02 mm/m 0.01 mm/m 0.005 mm/m 54 mm / 690 mm 20/10/5 microns for unit mm/m depending on the model, 11 unit mm/200 mm Color, Diagonal 46 mm / 1.8" fmax = 0.04% of MW, min. 0.01% of ME / 0.05%/h of ME +/- 15 degrees (approx. +/- 261 mm/m) < 3 seconds 0.1% of ME per °C 20°C +/- 10K from -30°C to +70°C Bluetooth and USB 2.0 Micro A Li-ion battery approx.10h uptime According to DIN 877 and DIN 2276-2, CE compliant and 1

Functions:

Absolute/relative measurement	Temperature compensation
Zero setting at any point	Remote View for Smartphone/PC via Bluetooth
Longitudinal and transverse inclination	Battery charge indicator
13 different units	Base length selectable
Hold function	Remote Control via smartphone/PC via Bluetooth (optional)
Semi-automatic calibration	Graphical WINDOWS-Software (optional)
Wireless communication	Measuring protocol (optional)

Scope of delivery:

- MICROLEVEL electronic horizontal spirit level
- Padded storage case

- USB charging and connection cable
- d storage case
- USB power supply and PC USB dongle
- Remote display download app
- Operating instruction

Special designs (optional): flat sole, magnetic equipment, holes for screwing on